

## **TECHNICAL SHEET**

### **TSP 410 – Finixa zinkspray 400ml**

#### **1. Product Overview:**

- Description: High-quality zinc spray designed for providing a protective coating to metal surfaces to prevent rust and corrosion.
- Application: Ideal for use in automotive repairs, industrial applications, and wherever metal protection is needed.

#### **2. Properties:**

- Color: Grey
- Physical State: Aerosol
- Density: 1.042 g/cm<sup>3</sup>
- Solubility: Moderately soluble in water, contains 79% organic solvent.

#### **3. Application Method:**

- Preparation: Ensure surface is clean, dry, and free from grease. Shake well before use.
- Application: Spray from a distance of approximately 25-30 cm in a well-ventilated area. Apply in thin, even layers, allowing sufficient drying time between coats.

#### **4. Drying Time:**

- Touch Dry: Depends on layer thickness, ambient temperature and humidity.

#### **5. Coverage:**

- Effective Coverage: Coverage may vary based on application thickness and substrate.

#### **6. Storage and Handling:**

- Storage: Store in a cool, well-ventilated place away from heat sources. Do not expose to temperatures exceeding 50°C.
- Handling: Use in a well-ventilated area. Wear appropriate personal protective equipment to avoid inhalation and contact with skin and eyes.

#### **7. Safety Precautions:**

- Flammability: flammable aerosol. Do not spray near open flame or sources of ignition.
- Protective Equipment: Use gloves, eye protection, and respiratory protection when necessary.

#### **8. Disposal:**

- Waste Management: Dispose of contents/container in accordance with local/regional/national/international regulations.

#### **9. Regulatory Information:**

- Meets relevant EU regulations for safety and environmental standards.

Note: For detailed health and safety guidelines, refer to the product's Safety Data Sheet (SDS).

This TDS is a concise summary intended for general guidance only. For specific applications or conditions, consulting the product's SDS or contacting the manufacturer directly is recommended.

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the product suitability for their own applications.*